



## SP & SP/IR SERIES SEMI-AUTOMATIC SKIN PACKAGING MACHINE



SP SERIES  
24" X 48" AND LARGER  
WITH OPTIONAL CASTERS  
AND FILM TEMPERATURE SENSOR



SP SERIES  
24" X 36" AND SMALLER  
WITH OPTIONAL CASTERS  
AND FILM TEMPERATURE SENSOR



SP/IR SERIES  
WITH OPTIONAL  
CASTERS, LIGHT CURTAINS AND  
AUTOMATIC FILM CLAMPING SYSTEM

**EXPERIENCE**  
*the* **STARVIEW**  
**ADVANTAGE**  
INNOVATIVE PACKAGING MACHINES

Starview Packaging Machinery, Inc.

Toll Free: 888-278-5555    [www.starviewpackaging.com](http://www.starviewpackaging.com)    [sales@starviewpackaging.com](mailto:sales@starviewpackaging.com)

# SP & SP/IR SERIES

## SEMI-AUTOMATIC SKIN PACKAGING MACHINE

### YOUR MARKET ... OUR SOLUTIONS

The **MSP Series** skin packaging machines are designed for low to medium volume applications. They incorporate a stationary heating system with instant on/off heaters, which come up to heat during cycles and turn off for loading/unloading.

The SP skin packaging machines have PLC timer control for precision repeatability and an accurate turbine regulator. A manual in-feed table, out-feed table and impulse type hot wire film cut-off are standard. These machines are a sturdy welded steel construction with removable panels for servicing.

The SP Series is available in the standard sizes beginning with 18 inches by 24 inches and also custom sizes.

For larger machines with additional automation and higher levels of production please consider our **ASP Series**.

## the **STARVIEW** **ADVANTAGE**

- A wide range of standard and custom size machines available to match customer requirements.
- The only pendant mounted color touch screen HMI in the industry for the ultimate in operator convenience and accessibility.
- A Starview exclusive remote access via standard Ethernet hardwire or optional Wi-Fi router gives management access to process information from the machine.
- Fully adjustable vacuum motor speed and oven power using an on-screen touch bar graph to provide precise film temperature and vacuum control.
- Machine operating recipe storage including all timer and bar graph settings with memory for up to 99 different recipes for operator recall of proven set-ups for complex products.
- Industry leading design, construction, features and customer support.



*more on next page*

# SP SERIES

## SPECIFICATIONS

|                         | SP-1824                        | SP-2430                        | SP-2436                        |
|-------------------------|--------------------------------|--------------------------------|--------------------------------|
| Max card size:          | 18" x 24"                      | 24" x 30"                      | 24" x 36"                      |
| Max product height:     | 10"                            | 10"                            | 10"                            |
| Heating system:         | Quartz impulse                 | Quartz impulse                 | Quartz impulse                 |
| Operator Light Curtain: | Optional                       | Optional                       | Optional                       |
| Average cycle time:     | 15-60 seconds                  | 15-60 seconds                  | 15-60 seconds                  |
| Electrical              | 208-240 Volts / 3 PH / 32 Amps | 208-240 Volts / 3 PH / 55 Amps | 208-240 Volts / 3 PH / 70 Amps |

|                         | SP-2448                         | SP-3036                        | SP-3048                        |
|-------------------------|---------------------------------|--------------------------------|--------------------------------|
| Max card size:          | 24" x 48"                       | 30" x 36"                      | 30" x 48"                      |
| Max product height:     | 10"                             | 10"                            | 10"                            |
| Heating system:         | Quartz impulse                  | Quartz impulse                 | Quartz impulse                 |
| Operator Light Curtain: | Standard                        | Standard                       | Standard                       |
| Average cycle time:     | 15-60 seconds                   | 15-60 seconds                  | 15-60 seconds                  |
| Electrical              | 208-240 Volts / 3 PH / 100 Amps | 208-240 Volts / 3 PH / 80 Amps | 208-240 Volts / 3 PH / 90 Amps |

|                         | SP-3648                         |
|-------------------------|---------------------------------|
| Max card size:          | 36" x 48"                       |
| Max product height:     | 10"                             |
| Heating system:         | Quartz impulse                  |
| Operator Light Curtain: | Standard                        |
| Average cycle time:     | 15-60 seconds                   |
| Electrical              | 208-240 Volts / 3 PH / 100 Amps |

Specifications and model availability are subject to change without notice.

more on next page

# SP/IR SERIES SPECIFICATIONS

|                         | SP/IR-1824                     | SP/IR-2430                     |
|-------------------------|--------------------------------|--------------------------------|
| Max card size:          | 18" x 24"                      | 24" x 30"                      |
| Max product height:     | 10"                            | 10"                            |
| Heating system:         | Radiant panel                  | Radiant panel                  |
| Operator Light Curtain: | Standard                       | Standard                       |
| Average cycle time:     | 15-45 seconds                  | 15-45 seconds                  |
| Electrical              | 208-230 Volts / 3 PH / 50 Amps | 208-230 Volts / 3 PH / 55 Amps |

|                         | SP/IR-2436                     | SP/IR-3036                     |
|-------------------------|--------------------------------|--------------------------------|
| Max card size:          | 24" x 36"                      | 30" x 36"                      |
| Max product height:     | 10"                            | 10"                            |
| Heating system:         | Radiant panel                  | Radiant panel                  |
| Operator Light Curtain: | Standard                       | Standard                       |
| Average cycle time:     | 15-45 seconds                  | 15-45 seconds                  |
| Electrical              | 208-230 Volts / 3 PH / 70 Amps | 208-230 Volts / 3 PH / 80 Amps |

*Specifications and model availability are subject to change without notice.*



REQUEST  
A  
QUOTE

Please request specific model quotations for complete pricing, specifications and options from your local distributor. Feel free to contact Starview to obtain the contact information for the authorized distributor in your area.



**Starview Packaging Machinery, Inc.**

Toll Free: 888-278-5555

[www.starviewpackaging.com](http://www.starviewpackaging.com)

[sales@starviewpackaging.com](mailto:sales@starviewpackaging.com)

Copyright 2022 Starview Packaging Machinery, Inc.

